

DEALER HOT WATER PRESSURE WASHERS

Portable Electric

Direct Drive | DHS Series

CHAFFEE-WARD CORPORATION



A Division of Kepner Equipment

This electric pressure washer is built for industrial cleaning on sites where proper ventilation may not be accessible. It features a top-fired heat exchanger that is completely accessible for troubleshooting.



DH-2003-SE0E2G

Pump

- Direct drive triplex piston General or Mi-T-M pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector
(Available as an option on SE0E1M and SE0E2M models)

Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord

Components

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance
- No. 1 or No. 2 diesel or kerosene fired burner
(Not approved for bio-fuel)

Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- 13-inch flat-free tires

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects, swivel and bend restrictors
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off



DEALER HOT WATER PRESSURE WASHERS

Portable Electric

Direct Drive | DHS Series

CHAFFEE-WARD CORPORATION



A Division of Kepner Equipment

Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DH-1002-SE0E1G	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	418 lb.	295 lb.
DH-1002-SE0E1M	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	Mi-T-M	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	410 lb.	237 lb.
DH-1502-SE0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	General	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	422 lb.	299 lb.
DH-1502-SE0E1M	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	Mi-T-M	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	414 lb.	291 lb.
DH-2003-SE0E2G	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	General	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	439 lb.	316 lb.
DH-2003-SE0E2M	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	Mi-T-M	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	431 lb.	308 lb.

Options:		
Part Number	Description	Fits Models
HX-0232	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1G
HX-0233	Adjustable thermostat - Operator is able to adjust outlet water temperature between 86°-248°F	1000 to 2000-PSI models
HX-0235	Hour meter - Displays number of hours unit has been in operation	1000 to 2000-PSI models
HX-0237	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	1000 to 1500-PSI models
HX-0238	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	1000 to 1500-PSI models
HX-0239	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1M
HX-0240	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2G
HX-0241	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2M
HX-0243	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	2000-PSI models
HX-0244	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	2000-PSI models
HX-0245	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1M
HX-0246	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1G

Accessories:		
Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	1000 to 2000-PSI models
850-0433	50-ft. x 3/8-inch high pressure hose - For when you need extra hose for added mobility	All models



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-20P,
20-amp plug